

NEW

KPSL/KPST

54 - 58 - 60 mm



Key features

- Very compact design
- Easy to integrate
- High speed printing



Characteristics	Unit	KPSL	KPST
Printing Speed (max)	mm/s	150 (12V) - 250 (24V)	100 (12V) - 150 (24V)
Printing Width	mm	56	52
Resolution	dot/mm		8
Number of Dots	dot		448
Number of Columns	column		28 or 37 max
Character Size	dot*dot		12 x 24 or 16 x 24
Resident Code Page	---	CP 437, 737, 850, 852, 858, 860, 862, 863, 865, 866, 1252, 1256 + EasyFont Compatible	
Bar Code Type	---	Code 39, 93, 128, Interleaved 2/5, UPC-A, UPC-E, JAN8 (EAN8) & JAN13 (EAN13), Codabar, PDF417	
Paper Width	mm	58 - 60	54
Paper Roll Diameter	mm		up to 200
Paper Thickness	µm	From 60 to 100	From 60 to 185
Paper Loading	---		Auto loading
Operating Voltage	VDC		12 or 24V
Power Consumption	W		75
Head Pulse Life	pulse		1*10 ⁸
Mechanical Reliability	Km		100
Dimensions (W*D*H)	mm		95 x 93 x 118
Weight	g		960
Operating Temperature	°C/F		- 25 to + 70 / -13 to + 158
Operating Humidity	% RH		20 to 85 (non condensing)
Cutter	---		Guillotine (full and partial cuts)
Cutter Life	cuts	1 Million	500 thousands
Data Buffer	Kbytes		4
Interface	---		RS232 or USB 2.0
Driver	---		Windows™ 00 / XP / Vista / Linux
CEM & Safety Standards	---	UL60950-1, CSA 22.2-60950-1, IEC60950, CE Class B, FCC Class B, C-Tick	
Sensors	---		Top of form and paper out
Accessories	---		Power supply

