

NEW



KPSM / KPSH

58 - 60 mm

Key features

- Compact and rugged design
- Easy to integrate
- High speed printing



Characteristics	Unit	KPSM	KPSH
Printing Speed (max)	mm/s	150 (12V) - 250 (24V)	
Printing Width	mm	56	
Resolution	dot/mm	8	
Number of Dots	dot	448	
Number of Columns	column	28 or 37 max	
Character Size	dot*dot	12 x 24 or 16 x 24	
Resident Code Page	---	CP 437, 737, 850, 852, 858, 860, 862, 863, 865, 866, 1252, 1256 + EasyFont Compatible	
Bar Code Type	---	Code 39, 93, 128, Interleaved 2/5, UPC-A, UPC-E, JAN8 (EAN8) & JAN13 (EAN13), Codabar, PDF417	
Paper Width	mm	58 - 60	
Paper Roll Diameter	mm	up to 200 (various angular position)	
Paper Thickness	µm	From 60 to 100	
Paper Loading	---	Auto loading	
Operating Voltage	VDC	12 or 24 V	
Power Consumption	W	75	
Head Pulse Life	pulse	1*10 ⁸	
Mechanical Reliability	Km	100	
Dimensions (W*D*H)	mm	95 x 120 x 118	125 x 120 x 118 / 126 x 289 x 118 (with paper roll holder)
Weight	g	960	960 / 1230 (with paper roll holder)
Operating Temperature	°C/F	- 25 to 70 / -13 to 158	
Operating Humidity	% RH	20 to 85 (non condensing)	
Cutter	---	Guillotine (full and partial cuts)	
Cutter Life	cuts	1 Million	
Data Buffer	Kbytes	4	
Interface	---	RS232 or USB 2.0	
Driver	---	Windows™ 00 / XP / Vista / Linux	
CEM & Safety Standards	---	UL60950-1, CSA 22.2-60950-1, IEC60950, CE Class B, FCC Class B, C-Tick	
Sensors	---	Top of form and paper out and bezel with paper jam detection	
Accessories	---	Power supply	Power supply, paper roll holder with paper low sensor (option), sens'n print (option)

