



TPSK  
60 mm

### Key features

- Cutter with integrated paper chute
- Extended temperature range for outdoor applications



Characteristics	Unit	TPSK
Printing Speed (max)	mm/s	100
Printing Width	mm	48
Resolution	dot/mm	8
Number of Dots	dot	384
Number of Columns	column	24 or 42
Character Size	dot*dot	12 x 24 or 16 x 24
Resident Code Page	---	CP 437, CP 858, user fonts
Bar Code Type	---	Code 39, 128 , Interleaved 2/5, UPC-A, UPC-E, JAN8 (EAN8) & JAN13 (EAN13)
Paper Width	mm	60
Paper Roll Diameter	mm	102
Paper Thickness	µm	60
Paper Loading	---	Clamshell™
Operating Voltage	VDC	12 or 24 V
Power Consumption	W	55
Head Pulse Life	pulse	1*10 <sup>8</sup>
Mechanical Reliability	Km	50
Dimensions (W*D*H)	mm	102 x 160 x 204
Weight	g	1700
Operating Temperature	°C/F	-10 to 70 / 14 to 158
Operating Humidity	% RH	20 to 90 (non condensing)
Cutter	---	Tear off blade with integrated paper chute
Cutter Life	cuts	300 K
Data Buffer	Kbytes	1
Interface	---	RS232 and TTL
Driver	---	Windows™ 98 / 00 / XP / Vista / CE - Linux
CEM & Safety Standards	---	UL60950-1, CSA 22.2-60950-1, IEC60950, CE Class B, FCC Class B, C-Tick
Sensors	---	Paper low, paper out, door open, paper jam detector
Accessories	---	Power supply

